

Environmental Class® PerfectMatch™ Particleboard Core Doors

NON-RATED (EPMP) and 20-MINUTE POSITIVE PRESSURE (EPMP-20PPFM - SINGLES and EPMP-20PP PAIRS) (13)

Product Features and Specifications	Interior Use Only
Thickness	1-3/4"
Maximum Size	EPMP Single: 4/0x8/0 Pair: 8/0x8/0 EPMP-20PPFM: ITS-WH and UL: Single: 4/0x8/0 EPMP-20PP: ITS-WH and UL: Pair: 4/0x8/0 (15) Double Egress: 8/0x8/0 (15)
Minimum Size	1-5 3/4x6/0 At least 40% of the door by weight is comprised of recovered fiber content as certified by scientific certification systems. (SCS)
Faces	Thermoset Polymer
Crossbands	Engineered Fiber
Stiles	EPMP-1 and EPMP-20PPFM: 1" LSL with edge banding or stained stiles to match face EPMP-20PP: 1-3/8" concealed intumescent stiles with edge banding or stained stiles to match face
Top and Bottom Rails	7/8 Mill Option Wider top & bottom rails available
Core Assembly Adhesive	Type II (water-resistant)
Core	Scientific Certification Systems (SCS) certified particleboard core (which complies with ANSI A208.1) 70% FSC (Forest Stewardship Council) mixed sources
Lite Openings (6)	<u>METAL VISION FRAMES OR WOOD MOULDING: W2 - W3 or W10</u> EPMP-1: Total area of openings not to exceed 1,296 sq. in. of visible glass or one continuous dimension of 38" W or 54" H * See Glazing Table
Other Detail Work (7, 10, 21)	* Fitting * Machining
Warranty	Limited Lifetime

*Refer to separate page for explanation of footnotes.



Note, Marshfield DoorSystems, Inc doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.

For more information call: 800-869-3667

